


Maximum permissible filling weight (for compressed gases filled by weight only)	Verification Body Logo	First Inspection (Year/Month)	Customisable Logo Area (Black and White)
M18x1,5 I CTS <b>xx/xxx/xxxxxx</b> x,xx KG 9,0 L PW300 at 15° C PT/PH450BAR		UN XXXX Gas name	
EN12245:2009 + A1:2011 I  XXXX/XX			
PET LINER FINAL: NLL			INSTRUCTIONS: 1) Valve screwing torque: 85 Nm 2) Before use, read carefully the user manual 3) Avoid storing without pressure
WARNINGS FILL IN ACCORDANCE WITH MANUFACTURERS ISTRUZIONI THIS CYLINDER MUST NOT BE SUBJECTED TO A VACUUM AVVERTENZE RIEMPIRE SECONDO LE ISTRUZIONI DEL FABBRICANTE QUESTA BOMBOLA NON DEVE ESSERE SOTTOPOSTA A VUOTO			
FIRST INSPECTION DATE/DATA PRIMO COLLAUDO: XX/XXXX		RETESTING / RICOLLAUDO	

Verification Body Number

Cylinder layout	Description and notes	Empty cylinder weight - Aluminum alloy	Empty cylinder weight - Stainless steel
Cylinder without finishings (bare cylinder)	Without finishings	3.80±0.24 kg 8.38±0.52 lbs	4.22±0.30 kg 9.30±0.66 lbs
Finished cylinder with transparent coating	Finished cylinder with transparent coating and rubber caps.	4.55±0.24 kg 10.03±0.52 lbs	4.97±0.30 kg 10.96±0.66 lbs
Finished cylinder with yellow or black sleeve	Finished cylinder with coloured sleeve (black or yellow), transparent sleeve and rubber caps.	4.85±0.24 kg 10.69±0.52 lbs	5.27±0.30 kg 11.62±0.66 lbs



Legend:

- ① Inner boss (internal nozzle)

THREADS	
STANDARD THREAD	M18x1.5 - EN ISO 15245-1
OTHER COMMON THREADS	M25x2.0 - EN ISO 15245-1
	17E - EN ISO 11363-1

- ② O-ring
- ③ Outer boss (external nozzle)
- ④ Colour coded upper rubber cap
- ⑤ Composite stratification layer
- ⑥ Optional exterior finishing
- ⑦ Bottom rubber cap
- ⑧ Internal PET liner

**CTS SpA Type 4 cylinders Data Sheet:  
9.0 lt 300 bar Technical Gases**

Working pressure: 300 bar (4361 psi)	Boss (nozzles) material: Anodized aluminum alloy OR Stainless steel
Test pressure: 450 bar (6527 psi)	Liner material: PET
Min. design burst pressure: >900 bar (13053 psi)	Reinforcement material: Carbon fiber + Epoxy resin
Water capacity: 9.0 L (549.21 cu. inch)	Exterior finishing: Customer specifications
Service life: non limited (NLL) according to EN 12245:2009 + A1:2011	Approved gases: UN 1002 Air, compressed; (green upper cap) UN 1013 Carbon Dioxide; (gray upper cap) UN 1066 Nitrogen, compressed; (black upper cap) UN 1046 Helium, compressed; (brown upper cap) UN 1006 Argon, compressed. (green upper cap)
Specifications: EN 12245:2009 + A1:2011; European Directive TPED 2010/35/UE; ADR 2021	



The image has the only purpose to represent the product.