







Verification Body Logo First Inspection Year/Month Customizable logo area (Black and White)

M18x1,5 CTS 18/355/BA28358 x,xxKG 2,0L PW300 at 15°C PT/PH450BAR TS:-50°C to 60°C	UN 1049 Hydrogen Compressed	 COMPOSITE TECHNICAL SYSTEMS
 1370-40° EN 12245 I  yyyy/mm		 Composite Technical Systems S.p.A Via Monsignor Faldutti, 9 33048 Chiopris Viscone (UD) ITALY www.ctsyt.com
WARNINGS FILL IN ACCORDANCE WITH MANUFACTURER'S ISTRUCTIONS THIS CYLINDER MUST NOT BE SUBJECTED TO A VACUUM AVVERTENZE RIEMPIRE SECONDO LE ISTRUZIONI DEL FABBRICANTE QUESTA BOMBOLA NON DEVE ESSERE SOTTOPOSTA A VUOTO	INSTRUCTIONS: 1) Valve screwing torque: 85 Nm 2) Before use, read carefully the user manual 3) Avoid storing without pressure	QR CODE
FINAL:>NNL	RETESTING/RICOLLAUDO:	

Verification Body Number

Cylinder layout	Description and notes	Empty cylinder weight - Aluminum alloy	Empty cylinder weight - Stainless steel
Cylinder without finishings (bare cylinder)	Without finishings	1.34±0.09 kg 2.95±0.20 lbs	1.76±0.09 kg 3.88±0.20 lbs
Finished cylinder with transparent coating	Finished cylinder with transparent coating and rubber caps.	1.61±0.09 kg 3.55±0.20 lbs	2.03±0.09 kg 4.48±0.20 lbs
Finished cylinder with yellow or black sleeve	Finished cylinder with coloured sleeve (black or yellow), transparent sleeve and rubber caps.	1.70±0.09 kg 3.75±0.20 lbs	2.12±0.30 kg 4.67±0.20 lbs



Legend:

- ① Inner boss (internal nozzle)
- ② O-ring
- ③ Outer boss (external nozzle)
- ④ Upper rubber cap
- ⑤ Composite stratification layer
- ⑥ Optional exterior finishing
- ⑦ Bottom rubber cap
- ⑧ Internal PET liner

THREADS	
STANDARD THREAD	M18x1.5 - EN ISO 15245-1
OTHER COMMON THREADS AVAILABLE ON REQUEST	

**CTS SpA Type 4 cylinders Data Sheet:
2.0 lt 300 bar Hydrogen**

Working pressure: 300 bar (4351 psi)	Boss (nozzles) material: Anodized aluminum alloy OR Stainless steel
Test pressure: 450 bar (6527 psi)	Liner material: PET
Min. design burst pressure: >900 bar (13053 psi)	Reinforcement material: Carbon fiber + Epoxy resin
Water capacity: 2.0 L (122.04 cu. inch)	Hydrogen mass: 42 g (1.48 oz)
Exterior finishing: Customer specifications	Developed pressure at 60°C: 349 bar (5062 psi)
Service life: non limited (NLL) according to EN 12245:2009 + A1:2011	Approved gases: UN 1049 Hydrogen, compressed
Specifications: EN 12245:2009 + A1:2011; European Directive TPED 2010/35/UE, ADR 2017 or European Directive PED 2014/68/UE	



The image has the only purpose to represent the product.