

Verification Body Logo First Inspection Year/Month Customizable logo area (Black and White) M18x1,5 XX/XXX/XXXXXXX PW310=4500psi PH465BAR=6743psi x,xx Kg=x,xx lb 6,8L=415cu in UN 1002 Compressed Air COMPOSITE TECHNICAL SYSTEMS Composite Technical Systems S.p.A Via Monsignor Faidutti, 9 33048 Chiopris Viscone (UD) ITALY www.ctscyl.com INSTRUCTIONS: 1) Valve screwing torque: 85 Nm 2) Before use, read carefully the user manual 3) Fill with Breathing Air according to EN 12021 or fill with Grade D Air according to CGA G-7 4) Avoid storing without pressure RETESTING DATE: Verification Body Number 1370 DURATION: 45 MINUTES ISO 11119-3 USA/M0852 FINAL: NLL WARNINGS FILL IN ACCORDANCE WITH MANUFACTURER'S ISTRUCTIONS. PET LINER - THIS CYLINDER MUST NOT BE SUBJECTED TO A VACUUM.		<table><tr><th>Cylinder layout</th><th>Description and notes</th><th>Empty cylinder weight</th></tr><tr><td>Finished cylinder with transparent coating</td><td>Finished cylinder with transparent coating and rubber caps.</td><td>3.47±0.23 kg 7.65±0.50 lbs</td></tr><tr><td>Finished cylinder with yellow or black sleeve</td><td>Finished cylinder with coloured sleeve (black or yellow), transparent sleeve and rubber caps.</td><td>3.70±0.23 kg 8.16±0.50 lbs</td></tr></table>	Cylinder layout	Description and notes	Empty cylinder weight	Finished cylinder with transparent coating	Finished cylinder with transparent coating and rubber caps.	3.47±0.23 kg 7.65±0.50 lbs	Finished cylinder with yellow or black sleeve	Finished cylinder with coloured sleeve (black or yellow), transparent sleeve and rubber caps.	3.70±0.23 kg 8.16±0.50 lbs			
Cylinder layout	Description and notes	Empty cylinder weight												
Finished cylinder with transparent coating	Finished cylinder with transparent coating and rubber caps.	3.47±0.23 kg 7.65±0.50 lbs												
Finished cylinder with yellow or black sleeve	Finished cylinder with coloured sleeve (black or yellow), transparent sleeve and rubber caps.	3.70±0.23 kg 8.16±0.50 lbs												
7 8 6 5 4 3 2 1 522±5 Ø159±2 Ø166±2		Legend: 1 Inner boss (internal nozzle) <table><tr><td rowspan="3">AVAIABLE THREADS</td><td>M18x1.5 - EN ISO 15245-1</td></tr><tr><td>M25x2.0 - EN ISO 15245-1</td></tr><tr><td>7/8" - 14 UNF - 2B</td></tr></table> 2 O-ring 3 Outer boss (external nozzle) 4 Upper rubber cap 5 Composite stratification layer 6 Optional exterior finishing 7 Bottom rubber cap 8 Internal PET liner	AVAIABLE THREADS	M18x1.5 - EN ISO 15245-1	M25x2.0 - EN ISO 15245-1	7/8" - 14 UNF - 2B								
AVAIABLE THREADS	M18x1.5 - EN ISO 15245-1													
	M25x2.0 - EN ISO 15245-1													
	7/8" - 14 UNF - 2B													
CTS SpA Type 4 cylinders Data Sheet: 45 minutes (6.8 lt) 4.500 psi UN - SCBA cylinder														
<table><tr><td>Working pressure: 4500 psi (310 bar)</td><td>Boss (nozzles) material: Anodized aluminum alloy</td></tr><tr><td>Test pressure: 6743 psi (465 bar)</td><td>Liner material: PET</td></tr><tr><td>Min. design burst pressure: > 13489 psi (930 bar)</td><td>Reinforcement material: Carbon fiber + Epoxy resin</td></tr><tr><td>Water capacity: 414.96 cu. inch (6.8 L) Duration: 45 minutes</td><td>Exterior finishing: Customer specifications</td></tr><tr><td>Service life: non limited (NLL) according to ISO 11119-3</td><td rowspan="4">Approved gases: UN 1002 Compressed Air (Breathing Air)</td></tr><tr><td>Specifications: UN - ISO 11119-3 Cylinders; Manufactured in accordance with §§ 178.35 and 178.69 - 71.</td></tr><tr><td colspan="2">Approval CA2019100512 Regulaotry Authority: 49 CFR §178.69 - 70 - 71</td></tr></table>		Working pressure: 4500 psi (310 bar)	Boss (nozzles) material: Anodized aluminum alloy	Test pressure: 6743 psi (465 bar)	Liner material: PET	Min. design burst pressure: > 13489 psi (930 bar)	Reinforcement material: Carbon fiber + Epoxy resin	Water capacity: 414.96 cu. inch (6.8 L) Duration: 45 minutes	Exterior finishing: Customer specifications	Service life: non limited (NLL) according to ISO 11119-3	Approved gases: UN 1002 Compressed Air (Breathing Air)	Specifications: UN - ISO 11119-3 Cylinders; Manufactured in accordance with §§ 178.35 and 178.69 - 71.	Approval CA2019100512 Regulaotry Authority: 49 CFR §178.69 - 70 - 71	
Working pressure: 4500 psi (310 bar)	Boss (nozzles) material: Anodized aluminum alloy													
Test pressure: 6743 psi (465 bar)	Liner material: PET													
Min. design burst pressure: > 13489 psi (930 bar)	Reinforcement material: Carbon fiber + Epoxy resin													
Water capacity: 414.96 cu. inch (6.8 L) Duration: 45 minutes	Exterior finishing: Customer specifications													
Service life: non limited (NLL) according to ISO 11119-3	Approved gases: UN 1002 Compressed Air (Breathing Air)													
Specifications: UN - ISO 11119-3 Cylinders; Manufactured in accordance with §§ 178.35 and 178.69 - 71.														
Approval CA2019100512 Regulaotry Authority: 49 CFR §178.69 - 70 - 71														
The image has the only purpose to represent the product.														